1998 INDEX

A

Airborne release of radioactive compounds from fire. *See* Radioactive compounds, airborne release from fire of
Aircraft carrier firefighting trainer, computer simulation for, 89–91
Aircraft fuel fire environment, evaluation of intumescent material in, 59, 60
Air plenums, accumulation of cable and other products in, 282
Alcohol level in blood and carbon monoxide toxicity, 39, 40, 42, 44–46, 48, 52, 54
Appreciation to Referees, 3
Aqueous film forming form (AFFF), 291
  metering of agent use in proportioning systems, 295, 304
  poly(ethylene oxide) compatibility with, 294, 299–300
  slipperiness of, 298
Arson, 248
ASTM codes and standards, 93, 95
ASTM E 84, 179
ASTM E 119, 179, 357
ASTM E 603–77, 252
Atmosphere, fire emissions into. *See* Radioactive compounds, airborne release from fire of; Swedish study, fire emissions into atmosphere
Attorneys, value of prescriptive codes to, 184–185
Authorities having jurisdiction, value of prescriptive codes to, 184
Azhakesan, M. A., 99

B

Bailey, J. L., 139
Bannister, William W., 291
Behavioral response to fires, 94, 189, 241–242, 289–290
Bigglestone (Harry C.) Award, 288
Biotite, physical and chemical properties of, 195
Birch plywood. *See* Plywood (PLY), combustion tests
Book reviews, 280, 372
Brushlinsky, N. N., 195
Budnick, Edward K., 156
Building and Fire Research Laboratory, NIST. *See* NIST
Building materials. *See also* Enclosure lining materials; Wood
  concrete, 141
  fire hazard assessment of, 177–187
  gypsum, 140–141, 356–362
  steel, 59, 356, 358–360
Buildings
  evacuations, software for, 281
  fire hazard assessment of new designs, 175–187
  high–rise (*See* High–rise buildings)
  wood pyrolysis in structure fires, effect on carbon monoxide levels of, 325–355
Burnthrough, upholstered furniture, 247, 260–261, 263–264

C

Cable, electrical, in air plenums, 282
California, standards for upholstered furniture construction, 250
Carbon dioxide, 53
  compartment fire test of wood pyrolysis, 328, 331, 335–348, 354
  emitted into atmosphere from fires, 266, 270, 273, 276
  extinguishing agents, total flooding test procedure for (*See* Total flooding test procedure for fire–suppressant agents)
Carbon monoxide and fire toxicity, 39–58
  age as factor, 42–50, 53–54
  alcohol in blood as factor, 39, 40, 42, 44–46, 48, 52, 54
  gender as factor, 44–46, 48
  large databases, analyses of, 44–50
  physiological effects of carbon monoxide, 40, 50–52
Carbon monoxide emitted into atmosphere from fires, 266, 267, 270, 273, 276
Carbon monoxide levels in structure fires, wood pyrolysis as factor in, 325–355
  data analysis, 329–334
  door openings, compartments with, 326–328, 330, 333–334, 338–339, 351–352
  experimental methods, 326–329
  hallways, carbon monoxide leakage from compartment to, 326–329, 332–334, 348–352, 354
  window openings, compartments with, 326, 333–338, 351–352
Carboxyhemoglobin (COHb) and fire toxicity and, 39–54, 325
Ceiling/floor conduction, heat transfer through. *See* Vertical heat transfer through ceiling/floor conduction, algorithm to predict
Ceiling–mounted sprinklers for glazing protection, 121–122, 133–137
Cellulose
  fabric coverings for upholstered furniture, 249, 251, 252, 260
  radioactive components released from fires involving, 307, 315–317
  RIFT test of, 220
Central Office Fire Risk Assessment (COFRA), 156–176
  computer program, 171–174
  fire risk value, 171
  fire safety parameters, 159–171
  fire safety policy, objectives, and strategies, 158–159
  methodology, 157–158
  structure, 158–163
  subparameters, 162, 164–171
Ceramic intumescent material, thermal characterization of, 59–71
  experimental evaluation of material performance, 60–61
  higher temperatures, characterization at, 61, 67–69
  kinetics of decomposition, 61–64
  material description, 59
  permeability, 61–62, 66–67
  porosity, 61–62, 67
  specific heat and heat of decomposition, 61–62, 64–65
  thermal conductivity, 61–62, 65, 69

thermal expansion, 61–62, 66, 69
CFAST computer program, 89
algorithm to predict heat transfer (*See* Vertical heat transfer through ceiling/floor conduction, algorithm to predict)
CFD model, aircraft carrier firefighting trainer, 89–91
Chen, Chien–Chung, 291
Chen, Eric B., 291
Children playing with cigarettes/matches, 248, 260
Chipboard, 271. *See also* Melamine faced chipboard (MFC), combustion tests
Christian, Sherril D., 72
Cigarettes as ignition source, upholstered furniture, 247–250, 252, 254–257
Class A foam, 291
Codes and standards. *See also* specific NFPA standards
ASTM role in, 93, 95
performance-based, 185–187, 283–284
prescriptive, 178–185
Combustibility parameters for enclosure lining materials using RIFT
experimental procedures and test materials, 198–200
flame flux and related parameters, derivation of, 202–203
flame spread results, 203–208, 219–220
framework for data reduction, 201–203
heat of gasification and pyrolysis rate, 216–219
heat of gasification data reduction, 201–202
heat release rate data reduction, 201
heat release rate results, 203–204, 208–212, 219–220
mass loss rate data reduction, 201
mass loss rate results, 208–212, 219–220
pyrolysis rate and effective heats of gasification and combustion, 216–219
spreading flame flux results, 212–216, 220
Combustion efficiency and fire ventilation, 269
Compartment fires
post–flashover fires, effect of wood in upper level of, 325–355
sprinkler protection of glazing, 120–122
Compartment global equivalence ratio (CGER), 341–343
Compartment plume equivalence ratio (CPER), 329–332, 334, 341
Computational fluid dynamics (CFD) model, aircraft carrier firefighting trainer, 89–91
Computer programs. *See also* Fire simulations; HAZARD I computer programs
Central Office Fire Risk Assessment (COFRA), 171–174
CFAST, 89 (*See also* Vertical heat transfer through ceiling/floor conduction)
EVACNET4, 281
FAST, 228–229
Concrete, 141
Cone calorimeter system, reduced scale ignition and flame spread technique. *See* Reduced scale ignition and flame spread technique (RIFT)
Continuing education, 193–194
Corridors. *See* Hallways
Cost of Saving Lives, The, 1–2
Cummings, Bruce T., 291

D

Damage control firefighting, poly(ethylene oxide) hose stream additive use for, 293–294
Davis, William D., 89
Detection, fire. *See* Fire detection
Diethylene glycol butyl ether (DGBE), 295, 304
Dioxins, 266, 276–276
Donatelli, Alfred A., 291
Door openings, effect on carbon monoxide leakage from compartment fire, 326–328, 330, 333–334, 338–339, 351–352
Drag reduction, hose stream, 292
Drug–positive fire victims, and carbon monoxide toxicity, 42, 47
Dynamic programming for egress analysis, multiple objective, 227–246

E

Economics of fire protection, 283
Egress analysis, HAZARD I EXITT and multiple objective dynamic programming method compared, 227–246
Electrical cable, wire, and other products in air plenums, 282
Electrical insulation, flammability handbook for, 280
Electrical nonmetallic tubing (ENT), 356
Eliahu, Avi, 356
Emissions into atmosphere from fires. *See* Radioactive compounds, airborne release from fire of; Swedish study, fire emissions into atmosphere
Enclosure lining materials
combustibility parameters, RIFT (*See* Combustibility parameters for enclosure lining materials using RIFT)
ignition and opposed flame spread trials, RIFT, 103–111
End users, value of prescriptive codes to, 181–182
ENT (electrical nonmetallic tubing), 356
Environment, pollution of. *See also* Radioactive compounds, airborne release from fire of; Swedish study, fire emissions into atmosphere
Halon alternatives, 366–367
EVACNET4 computer program, 281
EXITT computer program compared to multiple objective dynamic programming, 227–246
Explosion protection, 190
Exterior glazing, sprinkler protection of. *See* Glazing, sprinkler protection of
Extinguishment methods. *See* Fire suppression

F

FAST program, 228–229
Fiberboard (FIBBD), combustion tests, 103, 107, 109, 200, 204, 207, 208
Finish ratings
gypsum wallboard, experimental tests on, 358–360
review of literature on, 357–358
use of term, 356
Fire analysis litigation, 184–185, 373
Fire barriers, use of, 59
FIREDATA, 228
Fire deaths. *See also* Carbon monoxide and fire toxicity
largest U.S. fires, 1991–1996, 180–181

New Jersey fire database, 1985–87, 40–41, 43
smoking materials, caused by misuse of, 248
Fire detection, 95–96, 188, 283, 373–374
exterior glazing protection, systems for, 126, 135
Fire emissions into atmosphere. *See* Radioactive compounds, airborne release from fire of; Swedish study, fire emissions into atmosphere
Firefighting, hose stream additives for. *See* Fluoroscein tracer as hose stream additive; Poly(ethylene oxide) hose stream additive
Firefighting trainer for aircraft carrier, computer simulation for, 89–91
Fire growth
ignition sequence for upholstered furniture, classification of, 263–264
multiple–hazards assessment and, 197
Fire hazard assessment, 92, 188–189, 377
inhalation and respiratory hazard, 307
multiple–hazards assessment of growing fires, 197
new designs and materials, value in evaluations of, 177–187
nuclear processing and waste facilities (*See* Radioactive compounds, airborne release from fire of)
Fire hose stream. *See* Fluoroscein tracer as hose stream additive; Poly(ethylene oxide) hose stream additive
Fire investigations, 373. *See also* Fire patterns
physical and chemical methods, 195
post–fire analysis, 282
Fire models. *See also* Computer programs; Fire simulations; Vertical heat transfer through ceiling/floor conduction, algorithm to predict; Zone models
computational fluid dynamics (CFD) model, aircraft carrier firefighting trainer, 89–91
fire-suppressant agents, total flooding test procedure; model calculations, 74–75
flame spread, ignitor and thickness effects on (*See* Upward flame spread, ignitor and thickness effects on)
NIST Fire Modeling and Applications Group, 89
smoke dispersion in buildings by stack effect (*See* Smoke dispersion in buildings by stack effect, simplified model of)
Fire patterns
NIJ Report 601–97: Full–scale Room Burn Pattern Study, 280–281
upholstered furniture (*See* Upholstered furniture, fire patterns on: smoldering *vs.* flaming combustion)
Fire protection
economics of, 283
safety concepts, optimization of, 190
Fire-resistant materials, intumescent. *See* Ceramic intumescent material, thermal characterization of
Fire retardant technology, 372
Fire risk assessment, 92, 188–189, 377. *See also* Central Office Fire Risk Assessment (COFRA)
Fire safety, nuclear power plants and installations, 286
Fire Safety and Technology: Turmoil, Progress, Opportunities, 372
Fire safety design, 375
Fire safety engineering
continuing education for professionals, 193–194
prescriptive codes, value of, 183–184
Fire safety requirements based on prescriptive codes and standards, 178–181
Fire safety science, 284–285
Fire service deployment analysis, 374–375
Fire simulations. *See also* HAZARD I
aircraft carrier firefighting trainer, 89–91
fuel fires, 60
window plume simulation, 124–125, 128–131, 135
Fire statistics. *See also* Fire deaths
New Jersey fire database, 1985–87, 40–41, 43
Sweden, fire damage in, 267–269
Fire suppression, 188, 373–374
Fire suppression agents
concentrations, instruments for measurement of, 365–366
environmental effects of, 268
Next-Generation Fire Suppression Program for Halon alternatives, 363–371
screening tests, 366–367
total flooding test procedure for (*See* Total flooding test procedure for fire–suppressant agents)
Fire tests
carbon monoxide in structure fires (*See* Carbon monoxide levels in structure fires, wood pyrolysis as factor in)
fire suppression agents, total flooding test procedure for (*See* Total flooding test procedure for fire-suppressant agents)
glazing, sprinkler protection of (*See* Glazing, sprinkler protection of)
history of, 179–180
laser-based instrumentation for, 365–366
LIFT (intermediate scale ignition and flame spread technique test), 99, 100, 109, 198, 220
RIFT (*See* Reduced scale ignition and flame spread technique (RIFT))
thermal characterization of a ceramic intumescent material (*See* Ceramic intumescent material, thermal characterization of)
upholstered furniture (*See* Upholstered furniture, fire patterns on: smoldering *vs.* flaming combustion)
upward flame spread (*See* Upward flame spread, ignitor and thickness effects on)
vertical heat transfer (*See* Vertical heat transfer through ceiling/floor conduction, algorithm to predict)
Fire toxicity and carbon monoxide. *See* Carbon monoxide and fire toxicity
Flame flux, enclosure lining materials. *See* Combustibility parameters for enclosure lining materials using RIFT
Flame spread. *See also* Reduced scale ignition and flame spread technique (RIFT)
opposed flow (*See* Opposed flow flame spread, RIFT use)
over vertical surfaces, 198
upholstered furniture (*See* Upholstered furniture, fire patterns on: smoldering *vs.* flaming combustion)
upward (*See* Upward flame spread, ignitor and thickness effects on)
wind-aided, 99
Flaming combustion, upholstered furniture. *See*

Upholstered furniture, fire patterns on: smoldering *vs.* flaming combustion
Flammability Handbook for Electrical Insulation, 2nd edition, 280
Flashover, 99–100, 198
early flashover times and flame spread time, 34
post-flashover compartment fires, effects of wood in carbon monoxide production in, 325–355
Fluoroscein tracer as hose stream additive, 291–306
experimental results, 296–298
field testing of treated water, 294–295
future experimentation, 303
nighttime and low light visibility of water stream, 292, 294, 296
proportioning systems, metering of agents in, 295–296
prototype injection and metering system, 302–303
use as tracer agent, 291
Foams, 291. *See also* Aqueous film forming form (AFFF)
Forney, G. P., 139
Fort Worth, Texas, Ramada Inn Central fire, 40–41
FORUM for International Cooperation on Fire Research, 283
Fuel fires, simulation of, 60
Full-scale Room Burn Pattern Study (NIJ Report 601–97), 280–281
Furniture, upholstered. *See* Upholstered furniture, fire patterns on: smoldering *vs.* flaming combustion

G

Gann, Richard G., 363
Gaseous agents, total flooding test procedure for. *See* Total flooding test procedure for fire-suppressant agents
Glazing, sprinkler protection of, 116–138
ceiling systems, 121–122
compartment fires, limitations on protection from, 120–122
exterior fire tests, 124–135
external fire exposure, 122–124
multisprinkler systems, 121, 136
orientation of sprinkler as factor, 120, 121
previous investigations, 117–120
single sprinklers, use of, 120–121
sprinkler activation time as factor, 121, 126–137
thermal shock due to cooling effect of water, 118, 128–137
water spray pattern as factor, 121, 126–128
Growing fires, multiple-hazards assessment of, 197
Gypsum
finish ratings of wallboards, 356–362
heat transfer, 140–141

H

Hagen, Arnulf P., 72
Hallways, carbon monoxide leakage from compartment fire to, 326–329, 332–334, 348–352, 354
Halon 1301 (CF_3Br)
Next-Generation Fire Suppression Program for alternatives to, 363–371
total flooding test procedure for, 74, 79–84
Hardboard (HDBD), combustion tests, 103, 107, 111, 200, 207, 209–210, 213–215, 218
Harmathy, T. Z., 6
Hazard assessment. *See* Fire hazard assessment
HAZARD I computer programs, 89
EXITT and multiple objective dynamic programming egress analysis compared, 227–246
Heat release rate (HRR)
enclosure lining materials (*See* Combustibility parameters for enclosure lining materials using RIFT)
upholstered furniture fires, 251
Heat transfer
algorithm to predict (*See* Vertical heat transfer through ceiling/floor conduction, algorithm to predict)
definition, 140
Heavy metals, 266, 276
High-rise buildings, 189–190
poly(ethylene oxide) hose stream additive use on fires, 293
smoke dispersion in (*See* Smoke dispersion in buildings by stack effect, simplified model of)
stairtowers, fire spread over painted surfaces in, 19
Hilado, Carlos J., 280
Hirschler, Marcelo M., 177
Hirst, Ron, 280
Hose stream additives, fluoroscein and poly(ethylene oxide). *See* Fluoroscein tracer as hose stream additive; Poly(ethylene oxide) hose stream additive
Human behavior in fire. *See* Behavioral response to fires
Human Behavior in Fire, 289
Hydrocarbons
adiabatic flame temperature calculations for fuel combustion, 75, 85–87
emitted into atmosphere from fires, 266, 276–278
unburned, compartment fire test of wood pyrolysis, 328, 331, 335–339, 342–343, 350
Hydrogen chloride (HCl), emitted into atmosphere from fires, 266, 270, 273
Hydrogen cyanide (HCN)
emitted into atmosphere from fires, 266, 270, 273, 276
fire toxicity and, 40, 42, 43, 44, 53

I

Ignition
in adjacent compartments due to conductive heat transfer, 139
measurement of opposed flow (*See* Reduced scale ignition and flame spread technique (RIFT))
Ignitor effects on upward flame spread. *See* Upward flame spread, ignitor and thickness effects on
Internal Ship Conflagration Control (ISCC) Program, 139
Intumescent material, thermal characterization of. *See* Ceramic intumescent material, thermal characterization of
ISO 9705, 34
ISO 56577, 100
ISO DIS 5660, 100, 104

J

Jones, W. W., 139

K

Kerosene, radioactive components released from fires

involving, 307, 311, 314
Kerr, Paul, 72
Kim, A. K., 116
King, Ralph, 280
King's Safety in the Process Industries, 2nd edition, 280
Koo, J. H., 59
Kostreva, Michael M., 227
Kushler, Brian D., 156

L

Lancaster, Laura C., 227
Laser–based instrumentation for fire test measurements, 365–366
Lattimer, Brian Y., 325
Lee, C. H., 18
Levine, R. Robert S., 89
Life safety, cost estimates and data on public risk management options, 1–2
Life Safety as a Design Parameter, 97–98
LIFT (intermediate scale ignition and flame spread technique test), 99, 100, 109, 198, 220
Liquid fuels
  boilover, 311, 314
  radioactive components released from fires involving, 307, 311, 313–315, 320–322
Lougheed, G. D., 116

M

Magnetometric method of investigating fire sites, 195
Manufacturers, value of prescriptive codes to, 182–183
Maritime firefighting. *See* Ships
Mass loss rate, enclosure lining materials. *See* Combustibility parameters for enclosure lining materials using RIFT
McKenna, Lawrence A., Jr., 156
Melamine faced chipboard (MFC), combustion tests, 103, 107, 111, 200, 207, 209–210, 212–215, 218
Metering agents for hose stream additives. *See* Fluoroscein tracer as hose stream additive
MIL-STD-1686A(AS), 59
Morales, Antonio J., 291
Multiple objective dynamic programming used for egress analysis, 227–246
Multistory buildings, smoke dispersion in. *See* Smoke dispersion in buildings by stack effect, simplified model of

N

Nelson, Gordon L., 39
New Jersey fire database, 1985–87, 40–41, 43
News and Meetings, 92, 188, 282, 372
New York City Fire Department, poly(ethylene oxide) additive tests, 292–293
Next-Generation Fire Suppression Program, 363–371
NFPA 70, 356, 358
NFPA 251, 179, 357
NFPA 255, 179
NFPA 914, 358
NFPA 921, 247
NFPA 80A, 123
NFPA Research Foundation, 92, 188, 282–283, 373–374
Nighttime and low light visibility of hose stream, 292, 294, 296
NIST, 96, 227, 283, 287, 377
  Fire Modeling and Applications Group, 89
  upholstered furniture, fire risk assessment of, 250, 252
Nitrates, radioactive. *See* Radioactive compounds, airborne release from fire of
Nitrogen, in chipboard binding material, 271
Nitrogen oxide (NOx), emitted into atmosphere from fires, 266, 270, 273, 276
No Fire A, evaluation of. *See* Ceramic intumescent material, thermal characterization of
Nuclear power plants and installations, fire safety in, 286

O

Ogle, R. A., 247
Opposed flow flame spread, RIFT use
  experiment, 104, 197–198
  results, 104–107
  theory, 101–103
Ordnance, fire resistant protection for, 59
Oxygen, in compartment fire test of wood pyrolysis, 328, 331, 335–340, 348–349, 354

P

Pareto optimal egress paths, 228
Parks, Lyman L., 156
Pendent sprinklers for glazing protection, 126, 132, 134
Perfluoromethylcyclohexane (PFMC) as extinguishing agent. *See* Total flooding test procedure for fire–suppressant agents
Performance–based codes and standards, 185–187, 283–284
Persson, Bror, 266
Petroleum fires, poly(ethylene oxide) hose stream additive use on, 293
Plasterboard, combustion tests, 103
Plastics. *See* Thermoplastic materials
Plenums, accumulation of cable and other products in, 282
Plywood (PLY), combustion tests, 103, 107, 111, 200, 207–210, 212–215, 218
Polyaromatic hydrocarbons (PAH), 276–278
Poly(ethylene oxide) hose stream additive, 291–306
  AFFF compatibility with, 294, 299–300
  drag reduction caused by, 292
  experimental results, 296–298
  field testing of treated water, 294–295
  firefighter staffing levels, effect on, 293, 302
  fish toxicity of, 301
  future experimentation, 303
  history of use of, 292–294
  hose line reaction forces, 301–302
  slipperiness of treated water, 293, 298–299
Polymer material, fire emissions from, 271
Polymethylmethacrylate (PMMA)
  flame spread on, 18–19, 27, 29, 31, 36, 99
  radioactive components released from fires involving, 307, 311–312, 315–318
  RIFT test of, 220
Polystyrene (PS), radioactive components released from fires involving, 307, 311–312

Polyurethane foam, upholstered furniture, 249, 251, 252
Post–fire analysis, 282
Prescriptive codes and standards
  appeal to users of, 181–185
  fire safety requirements based on, 178–181
Process industries, hazards of, 280
Protective clothing breathability project, 92, 376
Putorti, Anthony D., Jr., 280

Q

Quick–response sprinklers for glazing protection, 118, 120–122, 128–131, 133, 135–137
Quintiere, James G., 18, 288, 307

R

Radiation fire exposure tests, exterior glazing, 125–126, 131–135
Radioactive compounds, airborne release from fire of, 307–324
  combustion processes, 310–312, 319
  fire induced flow effects, 312–313, 319
  fire transport mechanisms, 308–313, 319–320
  liquid fuels, ARF fire data for, 313–315, 320–322
  solid fuels, ARF fire data for, 315–318, 320–322
Reduced scale ignition and flame spread technique (RIFT), 99–115, 196. *See also* Opposed flow flame spread, RIFT use
  analysis of results, 107–112
  enclosure lining materials, combustibility parameters for (*See* Combustibility parameters for enclosure lining materials using RIFT)
  ignition experiment, 103, 197–198
  ignition results, 104
  ignition theory, 100–101
  recommendations for use, 112
Residential fires, Sweden, 267
RIFT. *See* Reduced scale ignition and flame spread technique (RIFT)
Risk assessment
  telecommunications central offices (*See* Central Office Fire Risk Assessment (COFRA))
  upholstered furniture, 250
Risk management for life safety, 1–2
Roby, Richard J., 325

S

Safety science and technology, 190
Schumacher, J. L., 247
Separation distances, and external fire exposure, 123
Serapiglia, Michael J., 156
Shadwell, USS, 139, 143–154
Shafts, smoke dispersion through, 7–17
Shields, T. J., 99
Ships
  ceiling/floor conduction in (*See* Vertical heat transfer through ceiling/floor conduction, algorithm to predict)
  firefighting in internal spaces, poly(ethylene oxide) hose stream additive use for, 293–294
Sidewall sprinklers for glazing protection, 126, 128
Silcock, G. W. H., 99
Simonson, Margaret, 266
Sliepcevich, Cedomir M., 72
Smoke dispersion in buildings by stack effect, simplified model of, 6–17
  air flow, determination of, 7–14
  air leakage as factor, 6, 7, 10–12, 16–17
  interior and exterior temperatures as factor, 7
  smoke control measures based on, 16–17
  wind direction and intensity as factors, 6
Smoke toxicity, 39. *See also* Carbon monoxide and fire toxicity
Smoldering combustion, upholstered furniture. *See* Upholstered furniture, fire patterns on: smoldering *vs.* flaming combustion
Software review, 281
Solid fuels, radioactive components released from fires involving, 307, 311–312, 315–318, 320–322
Sprinkler protection of exterior glazing. *See* Glazing, sprinkler protection of
Stack effect, smoke dispersion in buildings by. *See* Smoke dispersion in buildings by stack effect, simplified model of
Stairtowers, fire spread over painted surfaces in, 19
Standards. *See* Codes and standards
Stark, USS, 139
Steel
  finish rating data for studs, 356, 358–360
  fire-resistant protection for members, 59
Steiner tunnel test, 179
Structure fires, effect of wood pyrolysis in carbon monoxide levels, 325–355
Sulfur dioxide (SO2) emitted into atmosphere from fires, 266, 273, 276
Swedish fire damage statistics, 267–269
Swedish Fire Protection Association, 267, 268
Swedish National Rescue Services Board, 267, 268
Swedish study, fire emissions into atmosphere, 266–279
  basis for determining toxic yield, 269–271
  car fires, emissions from, 273
  estimating total emission, 271–273
  extinguishment methods, emissions from, 268
  study results, 273–276
Synthetic materials, and fire safety requirements, 179–180
System safety, 93–94

T

Taber, B. C., 116
Tatem, P. A., 139
Technical Notes, 356, 363
Telecommunications central offices, fire risk assessment for. *See* Central Office Fire Risk Assessment (COFRA)
Thermal barriers, finish materials as, 356, 358
Thermal characterization of a ceramic intumescent material. *See* Ceramic intumescent material, thermal characterization of
Thermoplastic materials
  radioactive components released from fires involving, 311–312, 315–318
  RIFT test of, 220
  upholstered furniture, 249, 251, 260
Thermosetting polymers, RIFT test of, 220
Thickness effects on upward flame spread. *See* Upward

flame spread, ignitor and thickness effects on
Total flooding test procedure for fire–suppressant agents, 72–88
adiabatic flame temperature calculations for agents, 75–77, 85–87
apparatus, 73–74
chemical agent, calculations for, 77–83, 87
experimental results and model calculations, 74–75
extinguishment compositions calculation for agents, 77–83
physical agents, calculations for, 75–83, 85–87
Tucker, Edwin E., 72

U

U. S. Department of Defense, 363
U. S. Navy Research and Development Damage Control platform. *See Shadwell,* USS
Union Carbide Corporation, poly(ethylene oxide) additive tests. *See* Poly(ethylene oxide) hose stream additive
Upholstered furniture, fire patterns on: smoldering *vs.* flaming combustion, 247–265
asymmetric flame spread, 247, 261
construction of furniture, 248–250, 260–261
diffusion flames, 251
ignition location, 260–264
ignition sources, 247–250, 252, 254–261
smoldering–to–flaming transition, 250–251, 256
test procedure, 251–254
test results, 255–256
time of extinguishment, 263–264
Upholstered Furniture Action Council (UFAC), 250
Upward flame spread, ignitor and thickness effects on, 18–38
basic model, 20–26
burning rate function, 23–25
burnout, 23, 25–26, 29
computations, 26–29
energy release rate, 22–23
flame length, formula for, 22
other current models, discussion of, 31–34
present model, discussion of results for, 29–31
propagation criteria, 29–34
room–corner tests, applications to, 34–35
transient effects, 18, 20, 23, 27
Uranium. *See* Radioactive compounds, airborne release from fire of
Usmanov, Mirjulil, 195

V

Vehicle fires, emissions from, 273
Ventilated fires, combustion efficiency of, 269
Venting of fire through windows, 122–123
Vertical heat transfer through ceiling/floor conduction, algorithm to predict, 139–155
adjacent compartments heated by fire compartment, 142
basis of fire model, 140–141
boundary conditions, formulation of, 143
experimental procedure, 145
experiments, selection of, 143–144
instrumentation, 145–146
materials of compartment surfaces, 140–141
modeling procedure, 147–149
predictive equations used by model, 141–143
single–zone approximation, 143
test configuration, 144–145
Vertical shafts, smoke dispersion through, 7–17
Vertical surfaces, flame spread over, 198
Viewpoint, 176
Volatile agents, total flooding test procedure for. *See* Total flooding test procedure for fire–suppressant agents
Volatile organic compounds (VOC), 276–278

W

Wall flame spread, ignitor and thickness effects on upward. *See* Upward flame spread, ignitor and thickness effects on
Water as extinguishing agent, better use of, 368–370
Watts, John M., Jr., 1, 97, 156, 193, 289
Wind–aided flame spread. *See* Upward flame spread, ignitor and thickness effects on
Windows
fire venting through, 122–123
mullion depth, effect on sprinkler protection of, 121, 136
openings, effect on carbon monoxide leakage from compartment fire, 326, 333–338, 351–352
width, effect on sprinkler protection of, 120–121, 136
window plume simulation, 124–125, 128–131, 135
Wood
carbon monoxide concentrations in compartment fires, wood pyrolysis as factor in, 325–355
finish rating data for studs, 356, 358–360
fire emissions from, 273

Z

Zicherman, Joseph B., 356
Zone models, 89. *See also* HAZARD I computer programs
CFAST as, 140
compartment heat loss, 142